

# MOELLER STONE CARE

## PRODUCT SPECIFICATION

### HMK® R154 - STRIPPER - STAIN REMOVER

- Special cleaner to remove tar, paint, grease, old impregnators, wax treatments and film built up from regular cleaning products.
  - Loosens dirt and coatings, enabling easy and effective removal.
  - For all polished and unpolished natural and artificial stone surfaces.

HMK® R154 is a ready to use solvent based stripper for removing old impregnators, wax treatments, varnish film built up from regular cleaning products, asphalt and bitumen, grease and oils from all natural and artificial stone surfaces, ceramic and porcelain tiles, terracotta and brick and block paving. HMK® R154 loosens dried on dirt and coatings from surfaces, allowing for easy and effective removal.

**Instructions:** Protect adjacent surfaces. If under floor heating exists, switch it off and allow the surface to cool. Apply a generous coat of HMK® R154 undiluted onto the dry surface using a stiff brush, scrubbing brush or suitable pad and leave for 5 to 15 minutes. Do not allow to dry. After 5 to 15 minutes, scrub the area again vigorously. Afterwards clean the area thoroughly with HMK® R155 Intensive Cleaner - acid free diluted about 1:10 with clean water. Remove the dirty liquid and rinse the area again with clean water. If patches remain untreated after drying, repeat the treatment as necessary.

**Note:** Some coatings require several applications or may not allow for chemical stripping.

**Important:** Do not apply in direct sunlight. Do not apply on rubber, plastic, perspex, lacquered surfaces and solvent intolerant materials. If these areas are splashed, remove splashes and rinse thoroughly with clean water.

When using a wet vacuum we recommend that you add HMK® Z702 Defoamer to the water to regulate the amount of foam.

**Coverage:** About 5-10m<sup>2</sup>/litre.

**Warning:** Chemical product. Contains naphtha, petroleum product. Flammable. Keep away from heat and flame. Harmful or fatal if swallowed or inhaled. Ensure adequate ventilation during the application process. Avoid eye/skin contact and breathing vapour or mist. If exposed flush/wash with water and seek medical attention. Keep container closed and out of the reach of children. See Material Safety Data Sheet for more detailed information.

**Packaging:** 12 x 1 litre bottles/box; 2 x 5 litre cans/box; 2 x 10 litre cans/box.

**Storage:** Store in a cool place and keep lid tightly closed.

**Testing:** Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12° and above 25°C.

**Limitation of liability:** The liability of HMK® Moeller Stone Care for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care shall not be liable for any consequential damages. No other warranty or representation is made or implied.