

MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH
 ZIEGELTALSTRASSE 2
 D-93346 IHRLEINSTEIN
 TELEFON 09441-176940
 TELEFAX 09441-1769499
 www.moellerstonecare.eu
 info@moellerstonecare.eu

MOELLER STONE CARE



PRODUCT SPECIFICATION

HMK® P326 - TERRACOTTA CARE

- **Self glossing treatment for terracotta, roof tiles and brick floors that enriches the color and structure of the surface.**
 - **Brings a brilliant silky shine to surfaces without buffing.**
 - **Reduces the penetration of water and dirt.**
 - **For interior use only.**

HMK® P326 is a concentrated care emulsion that enriches the color and structure of terracotta, brick and clay tiled floors and, gives a brilliant shine to the surface without the need for polishing. P326 develops a protective film that, with regular use, increases water and dirt resistance and makes textured and rough surfaces more resilient to heavy use and easier to care for. For interior use only. Do not use in wet areas such as shower cabins.

The HMK® P326 protective film can be removed and surfaces refreshed periodically with HMK® R155 Intensive Cleaner - acid free.

Important: When using HMK® P328 Terracotta Wax - natural or HMK® P329 Terracotta Wax - brown, HMK® P326 Terracotta Care must follow application to blend in any HMK® P328 Terracotta Wax - natural or HMK® P329 Terracotta Wax - brown unevenness. Allow HMK® P328 Terracotta Wax - natural or HMK® P329 Terracotta Wax - brown to cure for 48 hours prior to HMK® P326 application.

Instructions: If under floor heating exists, switch it off and allow the surface to cool. Clean the surface thoroughly and let it dry (max residual moisture of 2-4%). Shake well before use. For first time application, dilute HMK® P326 about 1:5 with clean water and apply thinly and evenly using a clean nonfraying cloth, sponge or mop. Apply to 5 to 10m² at a time wringing the applicator frequently in the same solution. Do not re-mop or rinse areas once cleaned. Replace the solution when it becomes dirty. For very absorbent surfaces, use a more concentrated mixture. Buff to higher shine using a regular floor machine with a white/tan at 900-1,500 rpm. Buffing while HMK® P326 is still tacky produces a more consistent and higher shine.

To clean surface thoroughly before treatment, use HMK® R155 Intensive Cleaner - acid free.

The shine is maintained if you occasionally add 100-200ml of HMK® P326 for every 10 liters of wash water. Use HMK® P324 Liquid Stone Soap for daily cleaning and alternate with HMK® P326 twice weekly, or as needed.

Coverage: About 50 to 100m² per litre.

Warning: Chemical product. Keep out of the reach of children and safe from frost.

Packaging: 12 x 1 litre bottles/box; 2 x 5 litre cans/box; 2 x 10 litre cans/box.

Storage: Store in a cool place.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12° and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stone Care for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care shall not be liable for any consequential damages. No other warranty or representation is made or implied.