

MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH
 ZIEGELTALSTRASSE 2
 D-93346 IHRLEINSTEIN
 TELEFON 09441-176940
 TELEFAX 09441-1769499
 www.moellerstonecare.eu
 info@moellerstonecare.eu

MOELLER STONE CARE



PRODUCT SPECIFICATION

HMK® P335 - ANTIQUE MARBLE PASTE - light

- Ready to use stain for all honed, tumbled, sandblasted and bush-hammered marble, travertine and limestone.
- Creates an antique and rustic appearance and reduces the penetration of water and dirt.
 - For interior use only.

HMK® P335 is a ready to use stain made from natural oxidizing oils that enriches the color and structure of the surface of honed, tumbled, sandblasted, bush-hammered, riven and textured marble, travertine and limestone floors, fireplaces etc. HMK® P335 creates an antique and rustic appearance and reduces the penetration of water and dirt into the surface. To complete treatment HMK® P337 Antique Marble Finish Wax must be applied. For interior use only!

Important: To complete treatment HMK® P337 Antique Marble Finish Wax must be applied.

Instructions: If under floor heating exists, switch it off and allow the surface to cool. Clean the area thoroughly and let it dry (max. residual moisture of 2-4%). Ensure adjacent surfaces are protected. Shake well before use! Before HMK® P335 is applied ensure that the color mix is appropriate. If necessary add additional color pigment. Apply HMK® P335 generously and evenly with a soft paintbrush or a roller with short fibres and allow to dry. Re-apply the treatment to particularly absorbent surfaces as required but ensure that the previous application is fully dry before repeating the procedure. Once HMK® P335 is completely dry its effect can no longer be reversed. Allow to cure for 24 to 48 hours and then proceed with the application of HMK® P337 Antique Marble Finish Wax.

To clean the surface thoroughly before application use HMK® R155 Intensive Cleaner - acid free and for ongoing maintenance use HMK® P324 Liquid Stone Soap a no-rinse natural product.

Coverage: About 5-10m² per litre.

Warning: Chemical product. Do not walk on the treated surface until the procedure is completed. Ensure that any brushes, cloths and rollers used are burned or spread out to dry as there is a risk of self inflammation caused by auto-oxidation. Once application is completed, HMK® P335 can no longer be removed by chemical means. Do not use in temperatures below 12 and above 25°C. Keep out of the reach of children. See Material Safety Data Sheet for more detailed information.

Storage: Store in a cool place.

Packaging: 12 x 1 litre bottles/box.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12° and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stone Care for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care shall not be liable for any consequential damages. No other warranty or representation is made or implied.